# **ADAM-5091 ADAM-5095**

### 4-port RS-232 Module 2-port CAN Module with Isolation Protection



ADAM-5091

### **Specifications**

### General

- Certification - Connectors
- CE, FCC Class A, FM 1 x TB21
- Enclosure
- ABS+PC
- LED Indicators TX, RX (each port)
- Power Consumption 0.6 W (max.)

#### **Communications**

- Data Bits
  - 5, 6, 7, 8 TxD, RxD, RTS, TS, DTR, DSR, DCD, RI, GND

4

none, even, old

- Data Signals Parity
- Ports
- UARTs
- Speed
- 4 x 16C850 (128 byte FIFO) 50 ~ 115.2 kbps 1, 1.5, 2
- Stop Bits

#### Support standard Com Port with Share interrupt Note:

For ADAM-5550 Series (ADAM-5091)

## **Ordering Information**

ADAM-5091

4-port RS-232 Module with Share Interrupt

### Rohas COMPLIANT 2002/585C ADAM-5095 **Specifications**

### General

- Certification
- Connector
- Enclosure
- LED Indicator
- Power Consumption

### **Communications**

- CAN Controller SJA-1000 CAN Transceiver 82C250 CAN2.0 A/B
- Protocol
- CAN-H, CAN-L Signal Support 1Mbps
- Speed
- Protection
- Isolation Protection 1,000 V<sub>DC</sub>

Note:

only for ADAM-5550 series

### **Ordering Information**

ADAM-5095

2-port CAN Module with Isolation Protection

ADIANTECH Programmable Automation Controllers

All product specifications are subject to change without notice.



- CE, FCC Class A
- 2 x DB9-M
- ABS+PC
- TX (Yellow), RX (Green) For Each Port
- 1 W (max.)